

Date: 15 January 2021

CODE: 22-VER5

TECHNICAL DATA SHEET



FILL ALL GAPS

MULTI PURPOSE CONSTRUCTION

Stærk
The bonding power

This acrylic multi purpose filler, with its high quality and long lasting features is perfect for many jobs such as filling cracks and holes. It can adhere to most substrates and it has an fungal agent to prevent mould in high humidity areas. It requires minimal tools, produces no fumes and is very easy to clean up so the job can be done quicker and more efficiently. This filler is the necessary tool for all professional painters and DIYers. In compliance with: GREEN STAR LOW VOC.

RECOMMENDED USE

Doors & Windows

- For filling all gaps between window and door trims before painting.
- Covering up gaps into the corner of doors and window frames.

Wall Cracks & Joints

- Repairing and fixing all cracks or holes from joint movement.
- Creating smooth finish for painted surfaces on block or brick work.

Panels & Boards

- Filling all gaps and any seams on wall and ceiling panel work.
- Creating a seamless finish in all wall corners.

Skirting boards & Trims

- Forming flawless joint on skirting boards, trims and architraves that will be easy to paint over.

Cupboards & Cabinets

- Filling all joints between cabinetry or cupboards that need to be painted.
- Removing all openings between different fixtures and walls.

BENEFITS

Paintable

Is paintable and dries quickly and is it perfect for filling and sealing all the gaps and cracks. Great for surface preparation before painting.

Easy to clean

Because it is acrylic based product it is very easy to clean up with a wet rag or soapy water. This feature makes it a very easy and practical tool.

Mould Resistant

Low shrinkage and bonding to many surfaces makes it absorb the thermal movement. With this you can use less mechanical fasteners.

20y. Guarantee

Against cracking, peeling or crumbling under proper usage. We give one of the longest and comprehensive guarantees in the industry.

PROPERTIES

Density 1,33 g/cm
Curing Time +23°C/50% RH | 3 mm/24hrs
Application Temperature +5°C to +40°C
Temperature Resistance -20°C to +75°C
Coverage 15m for 5mm bead
Tensile Strength 1,40 N/mm²
Skin Formation 15 minutes | +25°C
Joint Movement 15% | 25°C

SUITABLE FOR

Fill All Gaps Multi Purpose Filler will cover all holes, gaps or cracks and prevent pests and dirt from coming in. Its the perfect tool for paint preparation that will adhere to:

- WOOD, MDF, PARTICLE BOARD
- PLASTERBOARD, PLYWOOD,
- CONCRETE, BRICKS, FIBRE CEMENT
- STONE, MARBLE, GLASS
- METAL, ALUMINIUM, PLASTIC

APPLICATION

Cut off the top of the cartridge, position the threaded adaptor to the cartridge. Cut the threaded adaptor on an angle corresponding to the joint width. Place the cartridge into gun and inject the joint with the filler.

Apply sufficient pressure to the filler to ensure good penetration and adhesion to the joint sides. The applied filler should be smoothed immediately with a wet cloth or spatula to clean off excess filler. Can be painted within 24 hrs. after application.

Staerk Fill All Gaps Multipurpose Construction is not suitable for areas with constant exposure to water and temperatures below 5C.

PACKAGING

300ML Cartridges , 24 Cartridges per box

STORAGE

Protect from freezing, store in a cool dry place below 25 C temperature to prolong its service life. Product must be used within 24 months of purchase.

GREEN STAR LOW VOC